



**ABCBLAST
CLEANING**

Operating Efficiency Savings through Specialist Blast Cleaning

ABC Blast Cleaning Ltd




- **Best Practices – Safety**
 - Equipment
 - Personal Protection
 - Blast Facilities

- **Best Practices – Standard blast for NDT**
 - Medium
 - Blast Nozzles
 - Post Blast – Good / Bad

- **Operating Efficiency Savings - Specialist Blast Cleaning**
 - Why
 - Trials
 - 3 Stage process
 - Outcome

Best Practices – Safety



Blasting Equipment



A blast pot is considered a pressure assembly and falls under the legislation of the European Pressure Equipment Directive 2014/68/EU (PED)

Best Practices – Safety

Blasting Personal Protection equipment



Best Practices – safety

Blast room and set up

Key Features

- Shut off door safety sensor
- Lighting
- Weld solid steel panel floor
- Screw conveyors or recycling medium pit
- Extraction system (LEV)
- Earth straps (static electricity discharge)
- Rubber curtain walls (for steel shot)
- Vision windows
- External safety shut down buttons

Equipment setup (example Rotor)

- Roller stand with journal protection or Knife stands
- Coupling protection
- Gland protection
- Task light
- Access equipment / scaffolding
- trailers



Best Practices – safety



On site

COST VS TIME & SPACE



IMPROVED QUALITY VS HAND PREPARATION




Bungs in casing to stop ingress

Best Practices – Standard blast for NDT



Blast Medium

Medium	Usage / typical application	Grain size / hardness / Specific Gravity	Cost comparison
Garnet 80 (US mesh size)	Single use Profiling steel for coatings / removing coatings	177 microns 8.0 mohs 4.0kg/dm3	60 bags (datum) 
Garnet 180-220 (US mesh size)	Single use – removal of scale from non critical parts	63-88 microns 8.0 mohs 4.0kg/dm3	45 bags
FEPA 80 – 100 Ali oxide	Recyclable – removal of scale on balance of plant / coatings	125-180 microns 9.0-9.2 mohs 4.0kg/dm3	29bags
FEPA180-220 Ali oxide	Recyclable – removal of scale for NDT turbine equipment	53-90 microns 9.0-9.2 mohs 4.0kg/dm3	25 bags
FEPA220 - 240 Ali oxide (micro-grit)	Recyclable – Blade path on steam turbine equipment	45-75 microns 9.0-9.2 mohs 4.0kg/dm3	17 bags
FEPA320 – 360 Ali oxide (micro-grit)	Recyclable – stage 2 surface improvement	22.8 microns 9.0-9.2 mohs 4.0kg/dm3	14 bags
Glass bead 75-150 (spherical)	Recyclable – stage 3 surface improvement / disc head work	75-150 microns 5.0 - 6.0 mohs 2.5kg/dm3	38 bags
Sponge A30	Recyclable & dust free* – HP steam chest in situ	Sponge containing 30 US Mesh aluminium	9 bags
Dry Ice	Specialist cleaning applications	N/A used to freeze/impact to remove surface impurities	Equivalent to 20 bags

Best Practices – Standard blast for NDT



Standard Nozzles



Specialist Nozzles




Best Practices – Standard blast for NDT



Blasting Outcome - Good

- Scale removed from all areas of the aero foil, root, shroud, back of shroud and surfaces/locations, to the clients specification
- Minimal parent material removed and no deformation of surface or geometry due to blasting e.g. trailing edges



- Knowing when to stop, reporting concerns and finding solutions
- Self and Peer inspection through out the blast process and completion
- At this stage of blasting we would expect a surface reading of approx. 1.2 Ra or better, dependent upon parent surface condition

Best Practices – Standard blast for NDT




Poor surface condition




Blasting Outcome – Bad

Removed material from trailing edge



Remaining Scale



Damage when cleaning back of shroud




Damage to neighbouring blade




Operating Efficiency Savings - Specialist Blast Cleaning




Surface finish - A process of altering a metal's surface through removing, adding, or reshaping and measuring it's 3 characteristics of surface roughness, waviness, and lay.



Why – To enable the flow of steam over the aero foil, creating minimum drag or turbulence across the surface. A number of studies demonstrate positive effect between the relationship of the fluid flow past an object (Reynold number) and surface roughness, on efficiency.



Measurements - Direct measurement method, showing arithmetic average of surface heights that have been measured across a surface. Ra = Roughness average in micrometer



Typical surface finish of a new blade 0.4um to 0.5um

Operating Efficiency Savings - Specialist Blast Cleaning



Parties involved -

Roger Pillar (Drax), Frank Andrusyk (ABC), Steve Haupt

Target –

Recover or improve original surface finish (approx. 0.4 – 0.5 Ra)

Improve turbine efficiency – 0.25%

Reduction in fuel due to increased efficiency

Trials –

Performed on spare Drax turbine blades

Blast for NDT had to be fully achieved first – Surface finish approx. 1.1 – 1.2Ra

Surface improvement stage(s), Numerous mediums from natural products (walnut shells), soda blasting, silicates, ali-silicate, aluminum oxides, glass bead.





Polished
datum
blade
0.28 Ra

Operating Efficiency Savings - Specialist Blast Cleaning



Surface Improvement Stage 1 – Blast Clean for NDT

- Medium - 180 – 220 Aluminium oxide
- Grain Size 53-90 microns
- Pressure – 20 to 60 psi
- Ra surface reading 1.163




*Graphical representation of a single peak/trough only

Operating Efficiency Savings - Specialist Blast Cleaning



Surface Improvement Stage 2 – Surface improvement

- Medium - 320 - 360 Aluminium oxide
- Grain Size 22.8 microns
- Pressure – 20 to 60 psi
- Ra surface reading 0.463




*Graphical representation of a single peak/trough only

Operating Efficiency Savings - Specialist Blast Cleaning



Surface Improvement Stage 3 – Surface improvement

- Medium - Glass Bead
- Grain Size 75-150 microns
- Pressure – 20 to 60 psi
- Ra surface reading 0.330



*Graphical representation of a single peak/trough only

Outcome

Drax

- Surface finished achieved – 0.350 to 0.550Ra across the HP module
- Improved efficiency 0.25% to 0.5% (overall 2% efficiency seen on module reseal)
- Reduction in efficiency derogation and drop off over the running campaign
- Reduced operating costs
- Improved surface condition and reduction of scale build-up on next outage

Drax Power Station – 9off HP modules completed to date

Other Operators Worldwide – 7off HP-IP & LP modules completed to date, with 2 more contracted for 2022/3